

TYPE	QXBL0.75	QXBL1.5	QXBL2.2	QXBL3	QXBL4	QXBL5.5	QXBL7.5	QXBL11	QXBL15	QXBL18.5	QXBL22
Power KW	0.75	1.5	2.2	3.0	4.0	5.5	7.5	11	15	18.5	22
Current A	2.4	4	5.8	7.0	8.8	12	17	24	32	39	45
Voltage V	380/400/415										
Speed rpm	1470										
Frequency Hz	50/60										
Insulation grade	F										
Immersion depth m	2	3	3	3.5	4	4	5	5	6	5.5	6
Air input m ³ /h	10	22	35	50	75	85	100	160	200	260	320
Aeration area kgO ₂ /h	0.37	1	1.8	2.75	3.8	5.3	8.2	13	17	19	24

Performance parameters of QXB(L)

Type	QSB0.75	QSB1.5	QSB2.2	QSB3	QSB4	QSB5.5	QSB7.5
Power (kw)	0.75	1.5	2.2	3	4	5.5	7.5
Current (A)	2.3	3.7	5.6	6.8	8.8	11.3	15
Voltage (V)	380/400/415						
Speed (r/min)	2900				1470		
Fre. (Hz)	50/60						
Insulation class	F						
Max. water depth	3	3.5	4	4	4.5	5	5.5
Air emission volumn (m ³ /h)	10	22	35	50	75	85	100
Aeration area (m ²)	3X2	4X3.5	5X4	6X4.5	7X5	7.5X6.5	9X7

Performance parameters of QSB

